



TUV PL-L

TUV PL-L 24W/4P 1CT/25

TUV PL-L lamps are compact UVC (germicidal) lamps used in professional water and air disinfection units. The compact size of the lamp allows for a small system design and design flexibility. TUV PL-L lamps offer almost constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Thanks to the single-ended lamp base, lamp replacement is easy.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- DANGER: Risk Group 3 Ultra Violet product. These lamps emit high-power UV radiation that can cause severe injury to skin and eyes. Avoid eye and skin exposure to unshielded product. Use only in an enclosed environment which shields users from the radiation.

Product data

General Information		Voltage (Nom)	
Cap-Base	2G11 [2G11]	87 V	
Main Application	Disinfection	Mechanical and Housing	
Useful Life (Nom)	9000 h	Cap-Base Information	4 Pins
System Description	-	Approval and Application	
Light Technical		Mercury (Hg) Content (Nom)	4.4 mg
Color Code	TUV	UV	
Color Designation	- [Not Specified]	UV-C Radiation at 100 hr	7.1 W
Depreciation at Useful Lifetime	15 %	Product Data	
Operating and Electrical		Full product code	871829121248500
Power (Nom)	24 W	Order product name	TUV PL-L 24W/4P 1CT/25
Lamp Current (Nom)	0.345 A		

TUV PL-L

EAN/UPC - Product	8718291212485
Order code	927903204007
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25



Material Nr. (12NC)	927903204007
Net Weight (Piece)	82.000 g

Dimensional drawing

Product	D1 (max)	D (max)	A (max)	B (max)	C (max)
TUV PL-L 24W/4P 1CT/25	18 mm	39 mm	290 mm	315 mm	320 mm

TUV 24W PL-L

Photometric data



XDP0_XUTUVPLL-Spectral power distribution Colour

