


Ceramic Metal Halide - Master CDM-T

Range of single-ended, compact, high-efficiency, discharge lamps with a stable colour over lifetime and a crisp, sparkling light. Long lamp life compared with incandescent and halogen lamps. Low heat output and UV-block for reduced fading risks. Available in small CDM-T, for use with ballast and ignitor or electronic gear.




Product ID	Overall Length	Diameter	Light Centre Length	Arc Length
	C max.	D max.	L nom.	O nom.
20W	103	20	56	4
35W	103	20	56	5
70W	103	20	56	7
150W	110	20	56	9

Dimensions in mm

MASTER CDM-T

Shortcode	Description	Wattage (W)	Cap Base	Luminous Flux	Average Lifetime (hrs)	Colour Temp (K)	Min Order Quantity	Carton Qty
CDMT20W830	MASTERC CDM-T 20W/830 G12 ICT/I2	20	G12	1800	12000	3000	1	12
CDMT35W942	MASTERC CDM-T 35W/942 G12 ICT/I2	35	G12	3150	12000	4200	1	12
CDMT70W942	MASTERC CDM-T 70W/942 G12 ICT/I2	70	G12	6600	12000	4200	1	12
CDMT150W942	MASTERC CDM-T 150W/942 G12 ICT/I2	150	G12	12000	12000	4200	1	12

Master CDM-T Elite



Product ID	Overall Length	Diameter	Light Centre Length	Arc Length
	C max.	D max.	L nom.	O nom.
35W	103	20	56	5
50W	103	20	56	6
70W	103	20	56	7
150W	110	20	56	9

Dimensions in mm

MASTER CDM-T ELITE

Shortcode	Description	Wattage (W)	Cap Base	Luminous Flux	Average Lifetime (hrs)	Colour Temp (K)	Min Order Quantity	Carton Qty
CDMTEL35W930	MASTER CDM-T Elite 35W/930 G12 ICT/I2	35	G12	4000	15000	3000	1	12
CDMTEL35W942	MASTER CDM-T Elite 35W/942 G12 ICT	35	G12	3800	15000	4200	1	12
CDMTEL50W930	MASTER CDM-T Elite 50W/930 G12 ICT/I2	50	G12	5400	15000	3000	1	12
CDMTEL70W930	MASTERC CDM-T Elite 70W/930 G12 ICT/I2	70	G12	7500	15000	3000	1	12
CDMTEL70W942	MASTERC CDM-T Elite 70W/942 G12 ICT	70	G12	7500	15000	4200	1	12
CDMTEL150W930	MASTERC CDM-T Elite 150W/930 G12 ICT/I2	150	G12	15000	15000	3000	1	12