

## HPI PLUS Quartz Metal Halide

Energy saving compact fluorescent lamp. Compact long-arc low-pressure mercury discharge lamp envelope consists of 6 parallel narrow fluorescent tubes.

**Features:**


- Ovoid, internally white coated outer bulb.
- 3-band technology resulting in high luminous efficacy, both initially and over long lifetime.
- Available in cool white and daylight colour appearance demonstrating good colour stability.
- "S"- type for direct retrofit for HPL lamps.
- "P"- type for use without protective front shield.

**Luminaires:**

- HPI Plus BU-P and BUS-P suitable for use in open luminaires.
- For other HPI Plus lamps a protective front glass is required.

**System:**

- Can be run on HPI-gear as well as on SON-gear ("Plus"-concept). The results in both light output and colour temperature are different.
- HPI Plus BUS and BUS-P types require an HPL-gear and no ignitor.



Product ID	Overall Length C max.	Diameter D max.
250W	226	91
400W	290	122

Dimensions in mm

### MASTER HPI PLUS OVOID COATED METAL HALIDE LAMPS (BASE UP,IGNITOR REQUIRED)

Shortcode	Description	Wattage (W)	Cap Base	Luminous Flux (lm)	Average Lifetime (hrs)	Colour Temp (K)	Min Order Quantity	Carton Qty
HPIP250WBUGES	HPI PLUS 250W BU E40.1CT/12	250	E40	20500	20000	4500	1	12
HPIP400WBUGES	HPI PLUS 400W BU E40.1CT/6	400	E40	32000	20000	4500	1	6

# HPI PLUS Quartz Metal Halide continued

## MASTER HPI PLUS OVOID COATED, (BASE UP, IGNITOR REQUIRED, PROTECTED)

Shortcode	Description	Wattage (W)	Cap Base	Luminous Flux (lm)	Average Lifetime (hrs)	Colour Temp (K)	Min Order Quantity	Carton Qty
HPIP250WBUPGES	MASTER HPI Plus 250W/745 BU-P E40 SLV/12	250	E40	18000	20000	4500	1	12
HPIP400WBUPGES	MASTER HPI Plus 400W/745 BU-P E40 SLV/6	400	E40	32500	20000	4500	1	6

## MASTER HPI PLUS OVOID COATED (BASE UP, SELF START, NO IGNITOR REQUIRED)

Shortcode	Description	Wattage (W)	Cap Base	Luminous Flux (lm)	Average Lifetime (hrs)	Colour Temp (K)	Min Order Quantity	Carton Qty
HPIP400WBUSGES	HPI-PLUS 400W BUS E40.1CT/6	400	E40	32500	20000	4500	1	6

## MASTER HPI PLUS OVOID COATED, (SELF START, NO IGNITOR REQUIRED, PROTECTED )

Shortcode	Description	Wattage (W)	Cap Base	Luminous Flux (lm)	Average Lifetime (hrs)	Colour Temp (K)	Min Order Quantity	Carton Qty
HPIP400WBUSPGES	MASTER HPI Plus 400W/745 BUS-P E40 SLV/6	400	E40	32500	20000	4500	1	6