# LuxSpace Gen II - Surface Mounted

LuxSpace Surface-mounted is designed for general lighting applications in offices and retail outlets. It features the latest LED technology, resulting in low power consumption compared to a typical CFL downlight, and delivers consistent light output, stable colour performance and high colour rendering. It is available in Mini and Compact versions. All offer a compact look and feel, and a perfect fit. They are very easy to install, and their long lifetime means an end to the hassle of relamping.

Features and Benefits

- Glare control (reflector optic)
- Good colour consistency and high colour rendering; extra sparkle
- Extremely long lifetime: more than five times longer than CFL lamps

Product ID	Height (mm)	Cutout (mm)
Mini - BCS488	295	200
Compact - BCS498	366	260

Dimensions in mm (Nominal)

LuxSpace Gen II - Surface Mounted

LUXSPACE GEN II - SURFACE MOUNTED

Family Name	LuxSpace Gen II - Surface Mounted	Unified Glare Ratio (UGR)	22
Model	Mini - BCS488 Compact - BCS498	Driver	External Fixed or DALI driver
Lumen/ Watt	**3000K** Mini - 1000lm/ 13W Compact - 2000lm/ 27W **4000K** Mini - 1100lm/ 13W Compact - 2200lm/ 27W	Dimmable	Yes, DALI compatible dimming
		Installation	Surface mounted
		IP rating	IP20
		Colour of housing	White
Correlated Colour Temperature (CCT)	3000K, 4000K	Application	Retail, Hospitality, Offices
Colour Rendering Index (CRI)	80	Accessories	N/A
		Reflector	Glossy
Flex and Plug	No	Suspension Height - min/max	N/A
Lifetime L70*	50,000 hrs	Maximum Run Length	N/A

* = When the fitting reaches 70% of full potential (new)

COMMERCIAL CODE	12NC	DESCRIPTION
LUXSPACE MINI SURFACE MOUNTED DOWNLIGHT		
BCS48813W3KDWHG	911401535701	BCS488 C 1xDLED-3000 PSD-E C WH
BCS48813W4KDWHG	911401535001	BCS488 C 1xDLED-4000 PSD-E C WH
LUXSPACE COMPACT SURFACE MOUNTED DOWNLIGHT		
BCS49827W3KDWHG	911401535301	BCS498 C 1xDLED-3000 PSD-E C WH
BCS49827W4KDWHG	911401535401	BCS498 C 1xDLED-4000 PSD-E C WH