



SmartBright LED Batten Gen2

SmartBright LED Batten G2 is an affordable replacement for T5 and T8 battens in indirect lighting solutions, such as pelmet or cove lighting. The product comes in a variety of lengths, and an excellent lifetime of 30,000 hours. The product also comes with a plug in the packaging, so is easy for installation.



Features and Benefits

- Patented glass diffuser: Better heat conduction, no embrittlement, no yellowing
- Longer life time: 30,000 hours
- Higher energy-efficiency : 79lm/w
- Lower TCO vs.TL5 batten triggered to replace conventional batten more easily
- Slim and narrow end cap designed for cove and shelf lighting
- 5 lengths, 3 colours, flexible, mix and match
- Power cable included for easier purchase



Product ID	Length (mm)	Width (mm)	Height (mm)
BN066C (600mm)	585.5	25.5	43
BN066C (1200mm)	1185.5	25.5	43

Dimensions in mm (Nominal)

SMARTBRIGHT LED BATTEN GEN2

Family Name	GreenPerform Batten
Model	BN066C
Lumen/ Watt	1108lm / 14W 967lm / 12W 836lm / 10.8W 555lm / 7W 311lm / 4W
CCT	3000K, 4000K, 6500K
Colour Rendering Index (CRI)	80
Flex and Plug	Power Cable (included)
*Lifetime (L70@25°C)	30,000 Hrs
Unified Glare Ratio (UGR)	n/a
Optics	Diffused Glass

Driver	Integrated
Dimmable	PSU (Fixed)
Installation	Surface Mounted
IP rating	IP20
Colour of housing	White
Application	Shop Window, Cove, Shelf, Convenience Store, Freezer
Accessories	Spare Mounting bracket and screw Connection Cable (0.2m or 0.6m)
Suspension Height - min/max	NA
Maximum Run Length	10 Pieces

* = When the fitting reaches 70% of full potential (new)